





Large hopper merchandises fresh coffee beans

Consumers can clearly see fresh whole beans in the large 2.2lb (1kg) hopper



Touchpad has two programmable portion sizes from 8 to 12oz (230 to 350ml) and 9 cafe style beverage choices, plus hot water





VirtualTOUCH™ Ready

With optional VirtualTOUCH technology, customers need only hover their finger over a button to make a selection

A PATH TO GREAT ESPRESSO

1 GRIND, TAMP, BREW

Beans descend from the large 2.2lb (1kg) hopper into an internal grinder.

High-quality precision burrs perform a clean-cut milling of the beans. A moment later, the coffee is tamped into a puck with precise dosage, and the brewing begins. Nine bar brew pressure used with a variable brew group creates rich, strong espresso.

MIXING



Engineered with three powder hoppers (two

3.3lb/1.5kg hoppers for larger demand flavors and a third 2.2lb/1kg hopper). Adjustable speed auger motors produce accurately portioned drink recipes.

TASTE



A highly efficient two-tank system (0.2gal/0.8L

tank for espresso, and .75gal/2.84L tank for solubles) assures ideal serving temperatures for all espresso and café beverages.



crescendo Features

- 9 bar brew pressure used with a variable brew group to produce an excellent single or double shot with beautiful crema
- Tamping sensor achieves consistently great coffee extraction
- Precision burrs for clean-cut milling of the beans and assurance of superior grounds distribution
- Ideal serving temperature of espresso and café beverages are achieved with our independently controlled two tank system. Engineered with three powder hoppers: two 3.3lb (1.5kg) hoppers for the larger demand flavors and a third 2.2lb (1kg) hopper that allows for additional flavors
- Adjustable speed auger motors produce great consistency of ingredient portioning
- With VirtuatTOUCH option, the operator selects and dispenses a beverage by hovering a fingertip in front of a selection button without touching the machine.

MODELS											
Product Number	Model	Finish	Shots/hr	Volts	Amps	Watts	Hertz	Plug	Cord	Shipping Weight	Agency
U.S. Market											
44300.0201	Crescendo	Black/SS	40	120	11	1300	60	NEMA 5-15p	Yes	46.3kg (102lb)	NSF. Intertek
44300.0240	Crescendo	Black/SS	40	120/ 208-240	13.5/15.3	2800/3670	60	NEMA L14-20P	Yes	46.3kg (102lb)	NSE Intertek
Canada Market											
44300.6201	Crescendo	Black/SS	40	120	11	1300	60	NEMA 5-15p	Yes	46.3kg (102lb)	NSF. of intertek
Europe, Middle East, Africa (EMEA) Market											
44300.0200	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	50	EURO	Yes	46.3kg (102lb)	C€
44300.0213	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	50	UK	Yes	46.3kg (102lb)	C€
Middle East Market											
44300.0221	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	60	N/A	No	46.3kg (102lb)	KSA (€
44300.0222	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	60	N/A	No	46.3kg (102lb)	KSA (€
Latin America (LATAM) Market											
44300.0212	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	60	N/A	No	46.3kg (102lb)	NSF. Intertek
44300.0219	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	60	Korea 16A	Yes	46.3kg (102lb)	
Asia Pacific Market											
44300.0202	Crescendo	Black/SS	40	220-240	11.5 - 12.2	2500 - 2900	50	N/A	No	46.3kg (102lb)	CE
44300.0215	Crescendo	Black/SS	40	230	11.4 - 12.1	2500 - 2900	60	Korea 16A	Yes	46.3kg (102lb)	ктс
44300.0216	Crescendo	Black/SS	40	230	11.5 - 12.2	2500 - 2900	50	China 16A	Yes	46.3kg (102lb)	(€ China
44300.0218	Crescendo	Black/SS	40	220	11.5 - 12.2	2500 - 2900	60		No	46.3kg (102lb)	(€ Taiwan
		Plumbing	: 20-90 PSI.	Machine su	pplied with 9.	525mm (3/8")	garden h	ose fitting	J.		

